


## V50Q | EAP | PLATE FIXING


'ERGONOMIC' CROWN TREAD POLYURETHANE TYRED WHEEL WITH ALUMINIUM CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	45	150.5	53	300	ball	V50Q 100 EAPJ P05	V51Q 100 EAPJ P05	V52Q 100 EAPJ P05
125	45	178	53	350	ball	V50Q 125 EAPJ P05	V51Q 125 EAPJ P05	V52Q 125 EAPJ P05
150	45	200	53	450	ball	V50Q 150 EAPJ P05	V51Q 150 EAPJ P05	V52Q 150 EAPJ P05
200	45	245	53	520	ball	V50Q 200 EAPJ P05	V51Q 200 EAPJ P05	V52Q 200 EAPJ P05

## V50Q | PT | PLATE FIXING

POLYURETHANE TYRED WHEEL WITH CAST IRON CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	49	150.5	53	350	ball	V50Q 100 PTJ P05	V51Q 100 PTJ P05	V52Q 100 PTJ P05
125	50	178	53	450	ball	V50Q 125 PTJ P05	V51Q 125 PTJ P05	V52Q 125 PTJ P05
160	50	205	53	800	ball	V50Q 160 PTJ P05	V51Q 160 PTJ P05	V52Q 160 PTJ P05
200	50	245	53	800	ball	V50Q 200 PTJ P05	V51Q 200 PTJ P05	V52Q 200 PTJ P05
250	50	294	53	1100	ball	V50Q 250 PTJ P05	V51Q 250 PTJ P05	V52Q 250 PTJ P05

**i** All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated